

SABA Primer Wood

primer for (teak) wood

Description

SABA Primer Wood is a 1-component primer for pre-treating wooden (teak) (deck) sections.

Field of application

The marine sector. SABA Primer Wood is very suitable for pre-treating wooden (teak) (deck) sections before they are sealed off with Sabacaulk or Sabatack and for pre-treating synthetic material deck parts before they are bonded.

Advantages

- resistance against water
- applied primer is visible because of the colour
- short drying time
- long open time

Method of use

For instructions for use, see the relevant info sheets on www.saba.nl

When working with a type of wood which is not specified, please contact your supplier.

Seal the container as soon as possible after use; this has a positive effect on the processing properties and the shelf life of the product.

Technical data

Basis	Isocyanates and polyacrylat with silane
Viscosity at 23 °C (EN 12092)	approx. 180 mPa.s
Density (EN ISO 2811-2)	approx. 1020 kg/m ³
Solids content	approx. 42 %
Flashpoint	approx. + 2 °C
Solvents	Ethylacetaat
Drying time (minimum)	60 minutes
Open time (maximum)	20 hours
Coverage	approx. 100 g/m ²
Working temperature	min. + 5 °C to max. + 35 °C
Storage temperature	min. + 5 °C to max. + 25 °C
Temperature resistance	min. - 30 °C to max. + 70 °C

Order information

Packaging	can with resealable lid
Contents	500 ml (contains 12 items)
Colour	black
Article no.	101063 AAT
Shelf life	12 months (in unopened packaging)

Other packaging on request. The shelf life may vary for large packaging.

Safety recommendations

For more information about safety, see the relevant SABA safety data sheet.



SABA Dinxperlo BV

Industriestraat 3 NL-7091 DC Dinxperlo PO Box 3 NL-7090 AA Dinxperlo T+31 (0) 315 658999 F+31 (0) 315 653989 E info@saba.nl www.saba.nl



Our recommendations and instructions for use are based on the present status of know-how and technique. Clients and users should evaluate our products by themselves, with regard to utilization and requirements of their own choice. We shall take no responsibility in case our products are not being used subject to our recommendations and/or instructions for use. Furthermore, General Terms and Conditions of SABA Dinxperlo BV, will apply to our recommendations, instructions for use and the delivery of our products.